

# Globalstor® ExtremeStor DI for RED Digital Cinema

## Performance Grid

CAMERA FIRMWARE	DATA RATE	MAX MODE	FRAME RATE	REAL-TIME HD-SDI PLAY-OUT			
				4K ANA	4K 16:9	4K HD	4K 2:1
BUILD 18	REDCODE 28	ON	23.98	✓	✓	✓	✓
			24	✓	✓	✓	✓
			25	✓	✓	✓	✓
			29.97	✓			
		OFF	23.98	✓	✓	✓	✓
			24	✓	✓	✓	✓
			25	✓	✓	✓	✓
			29.97	✓	✓	✓	✓
	REDCODE 36	ON	23.98	✓	✓	✓	✓
			24	✓	✓	✓	✓
			25	✓	✓	✓	✓
			29.97	✓			
		OFF	23.98	✓	✓	✓	✓
			24	✓	✓	✓	✓
			25	✓	✓	✓	✓
			29.97	✓	✓	✓	✓
BUILD 17	REDCODE 28	ON	23.98	✓	✓	✓	✓
			24	✓	✓	✓	✓
			25	✓	✓	✓	✓
			29.97	✓			
		OFF	23.98	✓	✓	✓	✓
			24	✓	✓	✓	✓
			25	✓	✓	✓	✓
			29.97	✓	✓	✓	✓
	REDCODE 36	ON	23.98	✓	✓	✓	✓
			24	✓	✓	✓	✓
			25	✓	✓	✓	✓
			29.97	✓			
		OFF	23.98	✓	✓	✓	✓
			24	✓	✓	✓	✓
			25	✓	✓	✓	✓
			29.97	✓	✓	✓	✓

Test performed March 2009 at the Globalstor Data Corporation testing lab. Depending on the footage, your test results may vary.  
 Globalstor® is not responsible for variances in playback rates with individual footage.